Index of eeml Functions

eeci_AddMember
Add a member to the set.

eeci_CopyMembers
Copy the set members.

eeci_DupMember
Duplicate a member.

eeci_FreeMember
Free the given member.

eeci_FreeSet
Free the given set.

eeci_FreeSetMembers
Free the members of the given set.

eeci_GetNthMember
Find a member in the set.

eeci_NewMember
Create a new member.

eeci_NewSet
Create an empty set.

eeml
EML API functions package.

eeml_AddCallBack
Add a Callback Function to a Part

eeml_AddParameters
Add Parameters to Base Part Structure

eeml_AoiFileNameGet
Get the AOI filename.

eeml_ArrowStyleButtonSet

eeml_ArrowStyleButtonSetup

eeml_ArrowStyleChooser
Get the arrow style chooser.

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS, Inc.

eeml_ArrowStyleChooserClientDataCreate
Create the arrow style data for a chooser client.

eeml_ArrowStyleGetArrowFromItem
Get the arrow style from a chooser item.

eeml_ArrowStyleGetItemForArrow
Create a chooser item from an arrow style.

eeml_ArrowStyleSelect
Display the arrow style chooser.

eeml_BatchIsOn
Returns the batch mode status.

eeml_BatchJobAdd
Adds/Queues the job in the Batch Manager job queue.

eeml_BatchModeTypeGet
Returns the batch mode type.

eeml_BatchModeTypeSet
Sets the batch mode.

eeml_BatchOff
Turns the batch mode to OFF.

eeml_BatchOn
Turns the batch mode to ON.

eeml_button
API functions package for the EML button.

eeml_ButtonArm
Change appearance of the button to be armed.

eeml_ButtonChooserItemRender
Special Chooser Client Callback for Buttons

eeml_ButtonColorItemGet
Dedicated function for Color Button Client

eeml_ButtonColorItemPut
Dedicated function for Color Button Clients.

eeml_ButtonDisarm
Change appearance of the button to be normal.

eeml_ButtonInstallChooserClient

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

eeml_ButtonToggle
Toggle the appearance of the button.

eeml_canvas
ERDAS Onscreen Graphics Package

eeml_CanvasAddWorkProc
Add a work procedure to a canvas

eeml_CanvasAllocColorCells
Allocates private colorcells and returns the pixel to draw with.

eeml_CanvasAltShowGrayOPixrect
Draws, with opacity, a grayscale pixrect into a canvas.

eeml_CanvasAltShowGrayPixrect
Draws a grayscale pixrect into a canvas.

eeml_CanvasAltShowPixrectUsingColorLut
Draws a single band of data in color, does NOT use dithering.

eeml_CanvasAltShowRGBPixrect
Draws a 3−band pixrect into a canvas

eeml_CanvasAltShowTrueGrayOPixrect
Draws a grayscale pixrect into a canvas using opacity.

eeml_CanvasAvailableColors
Returns the number of color cells that are available for allocatior

eeml_CanvasClear
clears the entire canvas to the background color.

eeml_CanvasContextChangeCanvas
Change the canvas pointer in an Eeml_CanvasContext

eeml_CanvasContextClearClip
Sets the contextsclipregiontothepassedregion.'

eeml_CanvasContextCopy
Copies one Eeml_CanvasContext to another.

eeml_CanvasContextCreate
Creates an Eeml_CanvasContext object to be used with the pas

eeml_CanvasContextDelete
Frees all data associated with the passed Eeml_CanvasContext

eeml_CanvasContextFlushGraphics

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Causes any buffered graphics actions to be performed immediat

eeml_CanvasContextGetStringExtents
Get the dimensions of a string if drawn with the passed context.

eeml_CanvasContextSetArcMode

eeml_CanvasContextSetBackground
Sets the background color used when drawing with this Eeml_C

eeml_CanvasContextSetClipMask
Sets the Clip Mask that will be used for rendering.

eeml_CanvasContextSetClipOrigin
Sets the Clip Mask Origin that will be used for rendering.

eeml_CanvasContextSetClipRegion
Sets the contextsclipregiontothepassedregion.'

eeml_CanvasContextSetColorMethod
Sets the colorMethod field of the Eeml_CanvasContext structure

eeml_CanvasContextSetDashes
Sets the dashed line pattern used by the canvas context

eeml_CanvasContextSetDrawMode
Sets the drawMode field of the passed Eeml_CanvasContext

eeml_CanvasContextSetFillRule
Sets the fillRule field of the passed Eeml_CanvasContext.

eeml_CanvasContextSetFont
Sets the font field of the Eeml_CanvasContext structure.

eeml_CanvasContextSetFontSpec
Sets the font field of the Eeml_CanvasContext structure using a

eeml_CanvasContextSetForeground
Sets the foreground color used when drawing with this Eeml_Ca

eeml_CanvasContextSetJustification
Sets the justification field of the Eeml_CanvasContext structure.

eeml_CanvasContextSetLineCap
Sets the capStyle field of the passed Eeml_CanvasContext

eeml_CanvasContextSetLineJoin
Sets the joinStyle field of the passed Eeml_CanvasContext

eeml_CanvasContextSetLineStyle

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Sets the lineStyle field of the Eeml_CanvasContext

eeml_CanvasContextSetLineWidth
Sets the width that will be used for rendereing lines.

eeml_CanvasContextSetStipple

eeml_CanvasCopyArea
Copy an area of pixels from one canvas context to another.

eeml_CanvasCreate
Create an onscreen Eeml_Canvas wired to a generic part using the screen.

eeml_CanvasCreateBitmapCanvasFromData
Creates a pixmap fron an Egda_BaseData

eeml_CanvasCreateBitmapCanvasFromDataWithSize
Creates a pixmap fron an Egda_BaseData

eeml_CanvasCreateComplex
Create an onscreen Eeml_Canvas wired to a generic part using

eeml_CanvasCreateComplexClipMask
Creates a clip mask from a polygon

eeml_CanvasCreateComplexFrameDisplayed
Create an onscreen Eeml_Canvas wired to a

eeml_CanvasCreateOffScreen
Create an offscreen drawing canvas

eeml_CanvasCreateOffScreenCopyVis
Create an offscreen memory canvas using the same

eeml_CanvasCreateStippleMask
Creates a clip mask given a stipple pattern.

eeml_CanvasCreateWithVisFunc
Create an onscreen Eeml_Canvas using the visual type specifie

eeml_CanvasDelete
Delete an eeml_Canvas.

eeml_CanvasDrawArc
Draw an arc using the specified canvas context

eeml_CanvasDrawBevelRect
Draws a beveled rectangle using three passed colors

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

eeml_CanvasDrawIcon
Draw an icon into a canvas.

eeml_CanvasDrawLine
Draws a single line

eeml_CanvasDrawPoint
Draws a point at the given x,y coordinate.

eeml_CanvasDrawPolygon
Draws an unfilled polygon

eeml_CanvasDrawPolyline
Draws a polyline

eeml_CanvasDrawRectangle
Draws an unfilled rectangle

eeml_CanvasDrawText
Draws the passed text string at x,y

eeml_CanvasDup
Duplicate the specified canvas in width height,

eeml_CanvasFillArc
Fill an arc using the specified canvas context

eeml_CanvasFillComplexPolygon

eeml_CanvasFillComplexPolygonOpacity
Draws a filled complex polygon.

eeml_CanvasFillPolygon
Draws a filled polygon

eeml_CanvasFillPolygonOpacity
Draws a filled polygon with opacity

eeml_CanvasFillRectangle
Draws a filled rectangle

eeml_CanvasFontSpecCreate
Allows the specification of fonts by attributes.

eeml_CanvasFontSpecFree
Frees the memory used by a font specifier structure.

eeml_CanvasFreeColorCells

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Frees previously allocated color cells.

eeml_CanvasGetCloseColorCells
Returns closest existing color cells to the passed values

eeml_CanvasGetCloseColorCellsFromDither
Returns closest existing color cells to the passed values

eeml_CanvasGetDimensions
Returns the pixel width and height of the canvas.

eeml_CanvasGetDrawingAreaDimensions
Returns the pixel width and height of the canvases form.

eeml_CanvasGetNamedColor
Returns the pixel width and height of the canvas.

eeml_CanvasGetPixelColor
Get the color of a pixel at a given point.

eeml_CanvasGetScreenInfo
Gets information about the type of display that that canvas is on

eeml_CanvasGetSetOfVisualChoices
Get a list of available visuals

eeml_CanvasHasInterrupt
Check for a user interrupt

eeml_CanvasHasScrollBars
A function to determine whether the canvas is showing scrollbars

eeml_CanvasListCreate
Create space to hold list of canvases.

eeml_CanvasListFree
Free a CanvasList structure.

eeml_CanvasPartDimensionGet
Get the dimension of canvas EML part.

eeml_CanvasPopCursor
Sets the cursor to the previous one saved on the stack

eeml_CanvasPositionCursor
Position the pointer on the canvas

eeml_CanvasPushCursor
Sets the cursor to display on the canvas, saving the existing one

eeml_CanvasReadBitmapFile

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Reads in the bitmap file and returns it as an eeml canvas.

eeml_CanvasReadXpmFile
Reads in the XPM file and returns it as an eeml canvas.

eeml_CanvasReadXpmFileWithBackground
Reads in the XPM file and returns it as an eeml canvas.

eeml_CanvasRefresh
Copy the offscreen canvas to the onscreen.

eeml_CanvasRefreshArea
Copy the offscreen canvas to the onscreen in specified area.

eeml_CanvasRemoveWorkProc
Remove a work procedure from a canvas

eeml_CanvasResize
Resize an offscreen canvas

eeml_CanvasRotate
Rotates the given canvas by specified angle.

eeml_CanvasScrollBarViz
Set the visibility of the scrollbars

eeml_CanvasScrollSizes
Get the sizes of the scrollbars.

eeml_CanvasSetCellColors
Sets colormap entries for the canvas represented in cc

eeml_CanvasSetCursor
Specifies the bitmap to be used to track the mouse pointer

eeml_CanvasSetDefaultCursor
return the cursor to the boring default

eeml_CanvasSetEventHandler
Sets the function that will handle all events reported by the canv

eeml_CanvasSetHScrollMax
Sets the maximum value of the horizontal scrollbar

eeml_CanvasSetHScrollMin
Sets the minimum value of the horizontal scrollbar

eeml_CanvasSetHScrollPage
Sets the page size used by the horizontal scrollbar

eeml_CanvasSetHScrollValue

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Sets the current value of the horizontal scrollbar

eeml_CanvasSetVScrollMax
Sets the maximum value of the vertical scrollbar

eeml_CanvasSetVScrollMin
Sets the minimum value of the vertical scrollbar

eeml_CanvasSetVScrollPage
Sets the page size used by the vertical scrollbar

eeml_CanvasSetVScrollValue
Sets the current value of the vertical scrollbar

eeml_CanvasShowGrayOPixrectUsingLut
Draws a grayscale pixrect into a canvas using opacity

eeml_CanvasShowGrayPixrect
Draw a grayscale pixrect into a canvas.

eeml_CanvasShowGrayPixrectUsingLut
Draws a grayscale pixrect into a canvas

eeml_CanvasShowOPixrectUsingColorLuts
Draws a single band of data in color with opacity, uses dithering

eeml_CanvasShowPixrectUsingColorLuts
Draws a single band of data in color, uses dithering

eeml_CanvasShowRGBOPixrectUsingLuts
Draws a 3−band pixrect into a canvas using opacity.

eeml_CanvasShowRGBPixrect
Draws a 3−band pixrect into a canvas

eeml_CanvasShowRGBPixrectDitherFlag
Draws a 3−band pixrect into a canvas

eeml_CanvasShowRGBPixrectUsingLuts
Draws a 3−band pixrect into a canvas using the specified LUTS.

eeml_CanvasShowSparsePixrectUsingColorLuts
Draws a single band of data in color, uses dithering

eeml_CanvasShowSparseRGBPixrectUsingLuts
Draws a 3−band pixrect into a canvas

eeml_CanvasShowSparseRGBPixStack
Draws a 3−band pixrect into a canvas

eeml_CanvasUpdateStart

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Begin a relatively long running update of a canvas part

eeml_CanvasUpdateStop
Stop the update of a canvas part.

eeml_CanvasWindowId
Get the X ID of a canvas.

eeml_cellarray
Cell Array Frame Part for EML

eeml_chart
Chart Frame Part for EML

eeml_ChartAddCursorPositionCB
Adds an application callback on the cursor inside the Chart area

eeml_ChartDeleteAllColumns
Deletes all columns of data that had previously been added usin
function.

eeml_ChartDeleteColumn
Deletes the specified column of data from the Chart.

eeml_ChartDisplayLegend
Displays the Chart Legend Editor.

eeml_ChartDisplayOptions
Displays the Chart Options Dialog.

eeml_ChartFindBestOptions
Compute Best Fit Min/Max defaults for a Chart Axis

eeml_ChartGetChartTitle
Returns the Title of the Chart.

eeml_ChartGetLegendName
Returns the Legend Name for the specified column

eeml_ChartHideMarker
Removes the Marker from the Chart.

eeml_ChartInstall
Install the Chart on a generic part.

eeml_ChartRemoveCursorPositionCB
Removes an application callback on the cursor inside the Chart

eeml_ChartSave
Saves the Current Chart to the specified File as annotation.

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

eeml_ChartSavePostEpsScript
Saves the Current Chart to the specified File as Encapsulated P

eeml_ChartSavePostScript
Saves the Current Chart to the specified File as PostScript.

eeml_ChartSetTool
Set the specified Tool in the Chart.

eeml_ChartShowMarker
Displays a vertical marker in the Chart Area and adds an applica

eeml_ChartUpdateAll
Update the entire Chart including the plots, Axis, and plot backgr

eeml_ChartUpdateDataSets
Update the plots in the Chart without redrawing the axes.

eeml_ChooserAppFuncs
Get the table of chooser application functions.

eeml_ChooserApply

eeml_ChooserCategorySelect

eeml_ChooserCategorySelectAndItem

eeml_ChooserClientAlternateDataGet
Get the Alternate Client Data From the Chooser Client

eeml_ChooserClientAttach
Attach a Client to its chooser.

eeml_ChooserClientChooserGet
Get a Chooser from a Client

eeml_ChooserClientCreate
Create a chooser client.

eeml_ChooserClientDataGet
Get the Client Data From the Chooser Client

eeml_ChooserClientFree
Free a chooser client.

eeml_ChooserClientGet

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Get the Client From the Chooser

eeml_ChooserClientGetItem
Return the Chooser Client Item.

eeml_ChooserClientItemSet
Set the client item.

eeml_ChooserClientMenuPost
Display the menu for a given client.

eeml_ChooserClientQuickMenuInstall
Install a quick menu for a chooser on a part.

eeml_ChooserClientSet
Set the Client of the Chooser to the input Client.

eeml_ChooserCreate
Create a new Chooser.

eeml_ChooserDataGet
Get the Client Data From the Chooser

eeml_ChooserDisplay
Display the Chooser, using the given options.

eeml_ChooserIsUp
Test for Presence of a chooser.

eeml_ChooserItemCopy
Copy a chooser item.

eeml_ChooserItemEditedSet
Tell the chooser that an item has been edited.

eeml_ChooserItemFree
Free a chooser item.

eeml_ChooserItemGet
Get current chooser item.

eeml_ChooserItemIsValidSet

eeml_ChooserItemRender
Render a chooser item.

eeml_ChooserItemSet
Set the chooser to the given item.

eeml_ChooserItemUnselect

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Make sure no item is selected in the item list.

eeml_ChooserOK

eeml_ChooserQuickMenuGet
Return the Quick Menu.

eeml_ChooserSelectItem

eeml_colorwheel
Color Wheel Frame Part for EML.

eeml_ConnectTabletDigitizer
Connect Application to Tablet Digitizer.

eeml_dialog
The EML Standard Dialog Package.

eeml_DialogCdrom
Display the CDROM Util frame

eeml_DialogError
Display the standard error dialog.

eeml_DialogFatal
Display the standard error dialog for a fatal/critical problem

eeml_DialogGetText
Query the User for Text

eeml_DialogMessage
Display the standard message dialog.

eeml_DialogNonModalMessage
Display the standard Non−Modal message dialog.

eeml_DialogSave
Display the standard Save Dialog.

eeml_DialogVersion
Display the Version Dialog

eeml_DialogWarning
Display the standard warning dialog.

eeml_DialogYesNo
Display standard yes/no frame.

eeml_DialogYesNoCancel

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Display the standard 3−way answer Dialog.

eeml_DialogYesNoCancelWithHelp
Display the standard 3−way answer Dialog w/bubble help for the

eeml_DisconnectTabletDigitizer
Disconnect the tablet from the client.

eeml_EditTextInsert
Insert the text in text part.

eeml_EventFlush
Flush all pending EML events.

eeml_FillStyleButtonSet

eeml_FillStyleButtonSetup

eeml_FillStyleChooser
Get the fill style chooser.

eeml_FillStyleChooserClientDataCreate
Create the fill style data for a chooser client.

eeml_FillStyleGetFillStyleFromItem
Get the fill style from a chooser item.

eeml_FillStyleGetItemForFillStyle
Create a chooser item from an fill style.

eeml_FillStyleSelect
Display the fill style chooser.

eeml_FindComponentInRoot
Search for the specified EML part in the EML hierarchy.

eeml_FindFrameInComponent
Find a Frame in a Component

eeml_FindMenu
Find a Menu

eeml_FindParentFrame
Returns the parent frame of a part.

eeml_FindTextString
Get the string from the modulesstringlistdatabase.'

eeml_frame

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

API functions package for the EML frame.

eeml_FrameBusyMeterCheck
Update the meter and check for cancel

eeml_FrameBusyMeterCreate
Create a Busy Meter

eeml_FrameBusyMeterDestroy

eeml_FrameBusyMeterTaskSet
Set the task name for the busy meter.

eeml_FrameContextGet
Returns the Context (callback data) of a frame.

eeml_FrameContextSet
Set the Context (callback data) for a frame.

eeml_FrameDefinedForScreenNumber
Has frame been set for a specific screen number through eml sc

eeml_FrameDisplay
Display the frame

eeml_FrameDisplayAt
Display frame at x,y.

eeml_FrameDisplayModal
Display the frame as a modal dialog.

eeml_FrameDisplayOnScreen
Display the frame on the specified screen.

eeml_FrameDisplayOnScreenWithGeometry
Display the frame on the specified screen with geometry.

eeml_FrameDisplayWithContext
Display a frame with a context.

eeml_FrameDisplayWithGeometry
Display the frame with specified geometry.

eeml_FrameFindPart
Find a named part in a frame.

eeml_FrameIsDisplayedModal
Check to see if a frame is being displayed modally.

eeml_FrameIsMenuBarPresent

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Checks if the frame has toolbar.

eeml_FrameIsModal
Check to see if a frame is modal.

eeml_FrameIsStatusBarPresent
Checks if the frame has toolbar.

eeml_FrameIsToolBarPresent
Checks if the frame has toolbar.

eeml_FrameIsUp
Is the frame displayed?

eeml_FrameLocIsSpecial
Test to see if location is Reserved.

eeml_FrameMenuBarEnable
Enable/Disable the menubar.

eeml_FrameMessageClear
Clear the message in the status area of the appropriate frame.

eeml_FrameMessageDisplay
Display the message in the status bar.

eeml_FrameMeterBarEnable
Enable/Disable the meter bar.

eeml_FrameMinimumSizeSet
Sets the minimum size for frames.

eeml_FramePartDup
Duplicate the entire frame part.

eeml_FramePartResize

eeml_FrameRemove
Removes the frame.

eeml_FrameSourceGet
Find the source frame for any part.

eeml_FrameSourceSet
Set the source for a frame.

eeml_FrameStatusBarEnable
Enable/Disable the status bar.

eeml_FrametitleSet

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Set a new title for the frame.

eeml_FrameToolBarEnable
Enable/Disable the toolbar.

eeml_FreeCommand
Free the command args.

eeml_generic
API to the EML generic part

eeml_GenericUpdateStart
Begin a relatively long running update of a generic part

eeml_GenericUpdateStop
Stop the update of a generic part.

eeml_GetButtonColor
Get the color of colorbutton.

eeml_GetContext
Get the Application Context of a Part

eeml_GetEMLDisplay
Get the Display pointer.

eeml_GetGlobalData
Return a pointer to Global data of the EML System.

eeml_GetNextCommand
Get Next Command from Queue

eeml_GetNumberPartValue
Get the number partsvalue.'

eeml_GetString
Get A String from the text data base.

eeml_GetStringPartValue
Get the string partsvalue.'

eeml_GetTheRoot
Return the Root of the EML System.

eeml_GetValues
Get a List of Parameter Values from a Part

eeml_GuiStyleColor
Get the Color Pixel for a given system component.

eeml_GuiStyleFont

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Return the font for a system component

eeml_GuiStyleSize
Get the size for a given system component.

eeml_histogram
API to the Custom Histogram for EML

eeml_Init
Initialize the Window System

eeml_IsPartDisplayed
Get the display status of part.

eeml_IsPartHidden
Get the hidden status.

eeml_LineStyleButtonSet

eeml_LineStyleButtonSetup

eeml_LineStyleChooser
Get the line style chooser.

eeml_LineStyleChooserClientDataCreate
Create the line style data for a chooser client.

eeml_LineStyleGetItemForLineStyle
Create a chooser item from an line style.

eeml_LineStyleGetLineStyleFromItem
Get the line style from a chooser item.

eeml_LineStyleSelect
Display the line style chooser.

eeml_LogStatus
Log a message in status log.

eeml_Menu
eeml Menu Package

eeml_MenuAddPostCallback
Add a Post Callback to a Menu

eeml_MenuFrameSet
Set the part associated with the frame which owns this menu.

eeml_MenuGetPostXY

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Get the XY Location of the Menu Posting

eeml_MenuIsPopup
Predicate to determine if the argument is a popup menu.

eeml_MenuIsPulldown
Predicate to determine if the argument is a Pulldown menu.

eeml_MenuItemCount
Count the number of items in a menu

eeml_MenuItemDisable
Disable a menu item.

eeml_MenuItemEnable
Enable a menu item.

eeml_MenuItemGetValue
Get the value of menu item.

eeml_MenuItemSetValue
Set the value of menu item.

eeml_MenuPictureMenuInstall
Install a Picture Menu on a Widget

eeml_MenuPictureMenuPost
Popup a Picture menu

eeml_MenuRemoveCallback
Remove the Post Callback from a Menu

eeml_ModuleContextGet
Get the context of module part.

eeml_NumberPartValueGet
Returns the number part value.

eeml_NumberPartValueSet
Set Value of a Number Valued Part

eeml_ParseVa
Parse the EML script file.

eeml_part
EML Part API functions package.

eeml_PartDisable
Disable an EML part.

eeml_PartDup

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Duplicate the part.

eeml_PartEnable
Enable an EML part.

eeml_PartFind
Return a Pointer to a Part

eeml_PartFree
Frees the part.

eeml_PartHide
Hide an EML part.

eeml_PartIsValid
Check the part.

eeml_PartMoveOffscreen
Change the Position of a Part (Offscreen)

eeml_PartNameGet
Get the ID string of the part.

eeml_PartResizeOffscreen
Resize a part.

eeml_PartShow
Show an EML part.

eeml_PartValueFunctionsDisable
Turns off the use of setvalue/getvalue functions.

eeml_PartValueFunctionsEnable
Turns on the use of setvalue/getvalue functions.

eeml_PictureListReplace
Replace the picturelist in the scrollist part.

eeml_popuplist
API functions package for the EML popuplist.

eeml_PopupListReplace
Replace a the popuplist on display.

eeml_PopupListReplaceSet
Replace a the popuplist with new list.

eeml_PopupListSelectByPos
Select an item is scrollist by its position.

eeml_PostMessage

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Deliver a message to a part with no arguments.

eeml_PostMessageWithArgs
Deliver a message to a part with arguments.

eeml_prjeditor
Erdas Projections parameters GUI Editor.

eeml_PrjEditor
Invoke the Erdas Projections Parameters Editor.

eeml_QueryYesNo
Query the User for a Yes or No

eeml_QueueCommand
Place Command on Queue

eeml_RegisterCommandProcessorFunc
Register an application command processor function.

eeml_RemoveCallBack
Remove a Callback Function

eeml_scrollist
API functions package for the EML scrollist.

eeml_ScrollListAddItem
Add an New Item to a Scrolling List.

eeml_ScrollListClear
Clear the contents of a scrolling list.

eeml_ScrollListDeleteItem

eeml_ScrollListReplace
Update the contents of a scrolling list.

eeml_ScrollListReplaceItems
Replace the contents of a scrollList

eeml_ScrollListReplaceSet
Replace the contents of a scrolling list.

eeml_ScrollListSelectByPos
Select an item is scrollist by its position.

eeml_ScrollListTopPosGet
Get the position of the current

eeml_ScrollListTopPosSet

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Set the position of the current

eeml_ScrollListUnselect
Return a list to an unselected state.

eeml_SetButtonColor
Set the color of colorbutton.

eeml_SetContext
Set the Application Context on a Part

eeml_SetCreateFromNumber
This function creates a single member set from a number.

eeml_SetCreateFromNumberArray
Create a multimember set from a string array.

eeml_SetCreateFromString
Create a Set from a string.

eeml_SetCreateFromStringArray
Create a multimember set from an array of strings.

eeml_SetCreateFromStringList
Create a set from a string list.

eeml_SetDoneFlag
Terminate the EML interpreter.

eeml_SetDuplicate
Duplicate the given set.

eeml_SetExtractFirstMember
Split a set into is first and remainging members.

eeml_SetFree
Free the given set.

eeml_SetInsertString
Insert a string in a set.

eeml_SetParameters
Set Parameters of Base Part Structure

eeml_SetValue
Set Value of a Part

eeml_SetValues
Set the Parameter Values in a Part

eeml_StringPartValueGet

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Returns the string part value.

eeml_StringPartValueSet
Set Value of a String Valued Part

eeml_stylechoosers
API functions package for the EML stylechoosers.

eeml_SymbolStyleButtonSet

eeml_SymbolStyleButtonSetup

eeml_SymbolStyleChooser
Get the symbol style chooser.

eeml_SymbolStyleChooserClientDataCreate
Create the symbol style data for a chooser client.

eeml_SymbolStyleGetItemForSymbolStyle
Create a chooser item from an symbol style.

eeml_SymbolStyleGetSymbolStyleFromItem
Get the symbol style from a chooser item.

eeml_SymbolStyleSelect
Display the symbol style chooser.

eeml_tablet
Erdas Tablet Digitizer Interface.

eeml_TabletDigitizerSetProjection
Set the otput projection for the tablet from the client.

eeml_text
API functions package for the EML text.

eeml_TextAppendLine
Append a text line.

eeml_TextChangedReset
Clear the text changed flag.

eeml_TextClearSelection
Clear the selection in the text part.

eeml_TextCopy
Copy the primary selection to the clipboard.

eeml_TextCut

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Cut the primary selection to the clipboard.

eeml_TextFontSet
Set a new font for the text part.

eeml_TextGetCursorPosition
Get the position of the insert cursor in the text part.

eeml_TextGetInsertionPosition
Get the position of the insert cursor in the text part.

eeml_TextGetLastPosition
Get the last character position of text part.

eeml_TextGetSelectionPosition
Get the position of the selection in the text part.

eeml_TextGetString
Gets the text in the text part.

eeml_TextGrabFocus
Grab focus of the text part.

eeml_TextHighlightOff
Highlight a portion of text.

eeml_TextHighlightOn
Highlight a portion of text.

eeml_TextIsChanged
Check the text is changed flag.

eeml_TextPaste
Paste the clipboard selection to the text part.

eeml_TextReplace
Replaces the text in the text part.

eeml_TextReplaceLine
Replace text line.

eeml_TextSetInsertionPosition
Set the position of insertion cursor in the text part.

eeml_TextSetSelection
Set the primary selection of text part.

eeml_TextSetString
Set the string in the text part.

eeml_TextSetTopLine

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Set the top line.

eeml_TextStyleButtonSet

eeml_TextStyleButtonSetup

eeml_TextStyleChooser
Get the text style chooser.

eeml_TextStyleChooserClientDataCreate
Create the text style data for a chooser client.

eeml_TextStyleGetItemForTextStyle
Create a chooser item from an text style.

eeml_TextStyleGetTextStyleFromItem
Get the text style from a chooser item.

eeml_TextStyleSelect
Display the text style chooser.

eeml_TranslateIdToFunction
Lookup an Id in a translation table.

eeml_TranslationIdTableCreate
Create a quicker form of a translation table.

eeml_TranslationIdTableFree
Free the space used by an id Translation Table.

eeml_TranslationTableGet
Get the translation table for part.

eeml_TranslationTableSet
Set the translation table for module part.

eeui_CAAppendColumn
Append a New Column to the CellArray

eeui_CAAppendRow
Append a new row to a cellarray.

eeui_CAAppendRows
Append One or More Rows to a CellArray

eeui_CAClearAll
Clear All of the Cells in the CellArray

eeui_CAClearCell

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Clear the contents of a single cell in a cellarray.

eeui_CAClearColumn
Clear a single column in a cellarray.

eeui_CAClearRow
Clear a single row in a cellarray.

eeui_CACloseEdit
Close any open cells or titles.

eeui_CADeleteColumn
Remove the last Column from the Cellarray

eeui_CADeleteRow
Delete one row from a cellarray.

eeui_CADeleteRows
Delete one or more rows from a cellarray.

eeui_CADeselectRow
Remove a Row From the Current Selection

eeui_CAGetExclusiveRow
Get the Number of the Current Row for an Exclusive Column

eeui_CAIsColumnSelected
Test to see if a column is selected.

eeui_CAMenuFunction
Invoke one of the CellArray menu functions.

eeui_CAPositionToCell
Set the upper left visible row and column.

eeui_CAPositionToColumn
Set the upper leftmost column .

eeui_CAPositionToRow
Set the uppermost visible row.

eeui_CARowIsVisible
Check to see if a row is visible

eeui_CAScrollToRow
Position a given row to the top of the cell array.

eeui_CASelectRow
Add a Row to the Current Selection

eeui_CASetBusy

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Set the cellarray to a busy state.

eeui_CASetExclusiveRow
Set the Current Row for an Exclusive Column

eeui_CAStringMLength
Return the length of a string in number of

eeui_CATopLeftCellPositionGet
Returns the row,col of top left cell.

eeui_CAUpdateAll
Update an entire cellarray.

eeui_CAUpdateCell
Update a single cell in a cellarray.

eeui_CAUpdateColumn
Update an entire column of a cellarray.

eeui_CAUpdateRow
Update an entire cellarray row.

eeui_CellArrayInstall
Install the cell array on a generic part.

eeui_ColorWheelGetIHS
Get the ColorWheel Color Value as IHS

eeui_ColorWheelGetRGB
Get the Color Value as RGB

eeui_ColorWheelInstall
Install ColorWheel Methods on a Generic Part

eeui_ColorWheelSetBlue
Set the Blue Component of the ColorWheel color.

eeui_ColorWheelSetGreen
Set the Green Component of the ColorWheel Color

eeui_ColorWheelSetHue
Set the Hue Component of the ColorWheel Color

eeui_ColorWheelSetIHS
Set the Color of the ColorWheel using IHS

eeui_ColorWheelSetInensity
Set the Intensity Component of the ColorWheel

eeui_ColorWheelSetRed

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,

Set the Red Component of the Color

eeui_ColorWheelSetRGB

Set the ColorWheel Color using RGB

eeui_ColorWheelSetSaturation

Set the Saturation Component of the ColorWheel Color

eeui_HistogramInstall

Install the custom Histogram part.

From ERDAS IMAGINE eeml On−Line Help. Copyright (c) 1982−1997 ERDAS,